




meccanica
Morellato



RS

RASAERBA PER MOTOCOLTIVATORI
MOWERS FOR MOTOR CULTIVATORS




MADE IN ITALY

RASAERBA RS MOWERS RS



Il **rasaerba RS** offre un ottimo supporto alla manutenzione di prati, giardini e parchi; è particolarmente adatto per lo sfalcio d'erba, garantendo un taglio regolare e uniforme.

- Applicabile frontalmente a qualsiasi tipo di falciatrice e motocoltivatore
- Leggero e facilmente manovrabile, senza sforzo da parte dell'operatore
- Lame oscillanti in metallo duro facilmente sostituibili
- Altezza di lavoro registrabile (con slitte o spessori nell'applicazione con ruote)
- Sicuro grazie alla dotazione di protezione in tubolare sagomato e tela antiusura a norme CE
- Sabbiatura e verniciatura a polveri a forno ad alta resistenza
- Garanzia 2 anni

The **mower RS** offers optimal support for the maintenance of fields, gardens and parks; it is especially indicated for grass mowing, granting a regular and even cut.

- Can be coupled frontally to any type of mower and motor cultivator
- Light and easily maneuverable
- Swinging blades in hardened steel, easily replaceable
- Easy-to-set working height (with skids or thicknesses on the wheels application)
- Safe thanks to the free-wheel and CE standards protections
- Sandblasting and oven powder coating
- 2 years warranty



Fig. 1 Rasaerba RS 55 e RS 70
Mower RS 55 and RS 70

Fig. 2 Applicazione ruote anteriori
Front wheels application





Fig. 3 Dettaglio trasmissione su RS
Transmission detail on RS

Fig. 4 Dettaglio lame e portalamme
Blades and blades holder detail







DI SERIE:

Attacco rapido o flangiato per motocoltivatore
 Moltiplicatore ad ingranaggi dotato di ruota libera
 Piatto portalamme robusto innestato direttamente all'albero del moltiplicatore
 Slitte di appoggio zincate regolabili in altezza
 Altezza della presa di forza dal suolo 22 - 24 cm
 Giri in entrata 900/1' ca.

STANDARD EQUIPMENT:

Quick or flanged coupling for motor cultivator
 Free-wheel inserted in the oil-bath gearbox
 Sturdy blades holding plate directly mounted on the gearbox shaft
 Galvanized skids adjustable in height
 22 - 24 cm distance between the power shaft (PTO) and the ground
 900 Rpm PTO speed ca.



MOD.	 (KW)	 (CM)		 (KG)
RS 55	4/ 5,5	55	2	41
RS 70	5,5/ 8	72	2	52
RS 55 per HONDA F560	3,5/ 4,5	55	2	40

OPTIONAL: Applicazione ruote anteriori (Fig. 2) Front wheels application (Fig. 2)